




MAMO SOLO



MAMO SOLO PL



MAMO SOLO-1



MAMO SOLO-2

PRODUCT INFORMATION:

Thermal energy:	77,2 kWh,	PL: 79,3 kWh
Energy efficiency:	89 %,	PL: 91 %
CO%:	0,08 %,	PL: 0,09 %
Heat storage capacity:		
	100% after 8,7 hours,	PL: after 9,7 hours
	50% after 30,4 hours,	PL: after 34,1 hours
	25% after 50,6 hours,	PL: after 56,8 hours

PRODUCT NUMBER:

Product	Product number	Weight kg	Height mm
MAMO SOLO	3S	2320	1824
MAMO SOLO-1	3S-1	2330	1824
MAMO SOLO-2	3S-2	2360	1824
MAMO SOLO PL	3SP	2780	1824

NEEDED FOR ASSEMBLY:

* Mortar 2 x 25 kg (not included in NunnaUuni delivery)

PL = Top connection

PRODUCT INFORMATION

	BAKING OVEN / BAKING SPACE		FIREWOOD			FLUE CALCULATION VALUES ⁽¹⁾				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Width [mm]	Depth [mm]	Length fireplace / cooker [cm]	Max amount of wood [kg]	Length baking oven [cm]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø	Temperature °C
Mamo Solo	384	548	33	20	-	172	-15	19	180	257
Mamo Solo PL	384	548	33	20	-	137	-15	19	180	257

FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]				FLUE CONNECTION MEASUREMENTS [mm]			INCOMING AIR			
	approx. 150x150	approx. 150x200	approx. 150x300	round Ø	[A]	[B]	[C]	Incoming air pipe location L [mm]	Replacement air unit	HRT	Burning air approx. m³/h
Mamo Solo	-	x	x	180-210	150-180	250	350	570	-	920006	35 - 50
Mamo Solo PL	-	-	-	180	-	-	-	570	-	920006	35 - 50

SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	According to EN 15250			
	Behind	On the sides	Top	Front
Mamo Solo	50	200	200	1000
Mamo Solo PL	50	200	200	1000

¹⁾ The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards. It is recommendable to contact chimney sweeper beforehand.

NOTES!

The recommended minimum flue height is 5 m with Ø180 mm. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue. In the picture you can see the Finnish version.

Country- and region-specific regulations must be adhered to when installing the fireplace

